



landscape • entertainment • architectural • hospitality • illumination

RXD-02 DIRECTIONAL LIGHTS





DIRECTIONAL LIGHTS RXD-02 SERIES



TYPE

SPECIFICATIONS

CONSTRUCTION:

COPPER: Copper bullet and cast brass adjustable swivel with 240° rotation
ALUMINUM: Aluminum bullet; matching cast aluminum adjustable swivel with 240° rotation

LENS: High impact clear tempered convex glass

O-RING: High temperature red silicone

LAMP SUPPLIED: 20w MR16 FL(BAB) 5000 hours average rating
 (35w max copper 50w max aluminum)

LAMP OPTIONS: We recommend 40,000 hour ARROW 3w LED (L24) or
 5w (-L36) or 7w (-L48) ARROW Super Saver LED

SOCKET: High temperature ceramic GU5.3 bi-pin with 250°C silicone lead wires


WIRING: Black 3 foot 18/2 zip cord from base of fixture (12v only)
 For 25 foot 16/2 fixture lead wire add -25F to catalog number.

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable
 (12/2, 10/2 or 8/2 only)

MOUNTING: FA-03 black 9" ABS stake threaded 1/2" NPS

FINISH: Copper - Unfinished only

Aluminum - Black texture polyester powder coat. Optional finishes available



RXD-02-COP

RXD-02-CAM



ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT
RXD-02-COP	Copper Bullet	20w MR16 FL(BAB)	3.0 lbs.
RXD-02-BLT	Aluminum Bullet	20w MR16 FL(BAB)	3.0 lbs.

LAMP AND STAKE **INSTALLED** TO SAVE YOU TIME AND MONEY

MOUNTING ACCESSORIES

STEM EXTENSIONS

- FA-01-BRS: 15" 381mm
- FA-03-BRS: 9.00" 229mm
- FA-03-LG: 9.00" 229mm
- FA-24-MD-CST-POST-BRS: 13" 330mm
- FA-24-MD-CST-POST2-BRS (telescopic): 16" 406mm
- C/FA-25-/26/-BRS: 20" 508mm
- C/FA-26-75W/-BRS: 20" 508mm
- C/FA-26-GFIC/-BRS: 26" 660mm
- FA-24-MD-CST-TREE /-BRS (10"-41"): 2.65" 67mm
- FA-24-MD-CST-BRS: 1.4" 36mm
- FA-24-MD-CST-PC/-BRS: 2.65" 67mm
- FA-24-TREE /-BRS (10"-41"): 26" 660mm
- FA-111-BRS: 4.75" 121mm
- FA-24-LG-CST/-BRS: 0.875" 22mm
- FA-24-LG-DH-CST/-BRS: 0.875" 22mm
- FA-24-LG-DH-SPUN-COP: 0.875" 22mm
- FA-30: 10" 254mm
- FA-31: 13" 330mm
- FA-32: 16" 406mm
- FA-33: 21" 533mm
- FA-34: 26" 660mm

BEAM/GLARE CONTROL ACCESSORIES

FA-08-21	Round 1/4" Hex Cell Louver
FA-11-RXD02-BLUE	Blue Tempered Glass Insert Lens
FA-11-RXD02-GREEN	Green Tempered Glass Insert Lens
FA-11-RXD02-AMBER	Amber Tempered Glass Insert Lens
FA-11-RXD02-RED	Red Tempered Glass Insert Lens
FA-98-02	Linear Spread Tempered Glass Lens
FA-104-36C16	Wide Spread/Softener Glass Lens for RXD-02 Copper Series
FA-104-RXD02ALUM	Wide Spread/Softener Glass Lens for RXD-02 Aluminum Series

JOB INFORMATION

Type: _____ Date: _____

Job Name: _____

Cat. No.: _____

Lamp(s): _____

Specifier: _____

Contractor: _____

Notes: _____

FOCUS INDUSTRIES INC.®
 25301 COMMERCIAL CENTRE DRIVE
 LAKE FOREST, CA 92630
 www.focusindustries.com
 sales@focusindustries.com
 (949) 830-1350 • FAX (949) 830-3390

Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT