




## Tubular T3/GY6.35 Base



### Key Features & Benefits

The new 12V T3 GY6.35 base LED series integrates a set of COB LED sources and is ideal to replace T3 GY6.35 base **Incandescent** and **halogen** bulbs. Available: 3W options. This bulb is highly versatile, which can be used in landscape lighting, deck lighting to reading lights and offers significant energy savings and environmentally friendly. Light output is 360° which is perfect for even dispersion applications.

### Technical Specifications:

Model Name	JQ-G635-C03K27[2700K]	JQ-G635-C03K30[3000K]
Photo		
Halogen Replacement	<b>30 Watt</b>	<b>30 Watt</b>
Operating Voltage:	9 ~ 18V DC/ AC	9 ~ 18V DC/ AC
Power consumption:	3 Watt	3 Watt
Dimmable:*	YES	YES
Dimensions:	0.98"x0.39"D	0.59"Lx0.28"Wx1.14"H
CRI:	83	83
CCT Option:	3000K	2700K,3000K
Luminous Flux:	300 lm.	300 lm.
Operating Temperature:	-20° C - +50° C	-20° C - +50° C
Storage Temperature:	-30° C - +60° C	-30° C - +60° C
IP Rating	IP67	IP67
Safety Certification:	<b>FCC Compliance</b>	<b>FCC Compliance</b>
Rated Lifespan:	>25,000hrs.	>25,000hrs.

**Notes:** Wattage +/- 10%; Lumen Values +/- 5Lms. CRI +/- 5% ; Dimmable\* fully tested with LUTRON® DVEL magnetic low voltage dimmer or electrical dimmer with minimum load