

## **Bayonet**Double Contact









## **Key Features & Benefits**

The new 12V **bayonet** double contact base LED series integrates a set of SMD LED sources and is ideal to replace bayonet double contact base **Incandescent** and **halogen** bulbs. Available: 2.5W, 3.5W options. This bulb is highly versatile, which can be used in landscape lighting, deck lighting to reading lights and offers significant energy savings and environmentally friendly. Light output is 360° which is perfect for even dispersion applications.

**Technical Specifications:** 

1 centiled specifications.		
Model Name	JQ-BD-A03K27 [2700K] JQ-BD-A03K30 [3000K]	JQ-BD-A04K27 [CCT:2700K] JQ-BD-A04K30 [CCT:3000K]
Photo	23 mm 41 mm 15 mm	51 mm ——————————————————————————————————
Halogen Replacement	30 Watt	35 Watt
Operating Voltage:	9 ~ 18V DC/AC	9 ~ 18V DC/ AC
Power consumption:	2.5 Watt	3.5 Watt
	Z.O Wall	J.J Wall
Dimmable: *	Yes	Yes
Dimmable: *	Yes	Yes
Dimmable: * Dimensions:	Yes 1.61" x 0.59"D 80 2700k,3000K,4500K	Yes 2"x 0.59"D
Dimmable: * Dimensions: CRI:	Yes 1.61" x 0.59"D 80	Yes 2"x 0.59"D 80
Dimmable: * Dimensions: CRI: CCT Option:	Yes 1.61" x 0.59"D 80 2700k,3000K,4500K	Yes 2"x 0.59"D 80 2700k,3000K,4500K
Dimmable: * Dimensions: CRI: CCT Option: Luminous Flux:	Yes 1.61" x 0.59"D 80 2700k,3000K,4500K 210 lm.	Yes 2"x 0.59"D 80 2700k,3000K,4500K 280 lm.
Dimmable: * Dimensions: CRI: CCT Option: Luminous Flux: Operating Temperature:	Yes 1.61" x 0.59"D 80 2700k,3000K,4500K 210 lm. -20° C - +50° C	Yes 2"x 0.59"D 80 2700k,3000K,4500K 280 lm20° C - +50° C

**Notes**: Wattage +/- 10%; Lumen Values +/- 5Lms. CRI +/- 5%; Dimmable\* fully tested with LUTRON© DILV magnetic low voltage dimmer or electrical dimmer with minimum load

Distributed by Yardillumination.com 120 North Pacific Street E-1 San Marcos, CA 92069 866-523-7774