

Ceiling Panel

Premium Series



Key Features & Benefits

This Ceiling Panel LED lighting provide much more energy efficiency than traditional CFL bulbs, allowing you to light a very large area with a lower energy bill AND the best lighting technology for a long, lasting bulb life. Available: 2"x2", 1"x4", 2"x4" panel size options.




ETL DLC Premier Listed; 5 years no-hassle warranty

Buying and using conventional bulbs and fixtures also means that you incur three times more maintenance as well as replacement costs, compared to LED lighting.

LED lighting is also free of environmentally harmful Mercury as well as Halogen chemicals.

Widely used in commercial buildings, retailers, schools, hotels, etc.

Technical Specifications

Model Name	JQ -PL22-A30K40 JQ -PL22-A30K50	JQ -PL14-A30K40 JQ -PL14-A30K50	JQ -PL24-A40K40 JQ -PL24-A40K50
Photo			
Bulbs Replacement	100W	100W	150W
Operating Voltage:	120 - 277 V 60Hz	120 - 277 V 60Hz	120 - 277 V 60Hz
Power consumption:	30 Watt	30 Watt	40 Watt
Dimmable:	YES	YES	YES
Dimensions:	2'x2'	1'x4'	2'x4'
CRI:	>82+	> 82+	>82+
CCT:	4000K/5000K	4000K/5000K	4000K/5000K
Luminous Flux:	>125 lm/W	>125 lm/W	>125 lm/W
Operating Temperature:	-20° C - +50° C	-20° C - +50° C	-20° C - +50° C
Storage Temperature	-30° C - +60° C	-30° C - +60° C	-30° C - +60° C
Safety Certification:	UL/DLC Premium FCC Compliance	UL/DLC Premium FCC Compliance	UL/DLC Premium FCC Compliance
Rated Lifespan:	50,000hrs.	50,000hrs.	50,000hrs.

Notes Wattage +/- 10%; Lumen Values +/- 5Lms. CRI +/- 5%;

Distributed by Yardillumination.com

120 North Pacific Street E-1
San Marcos, CA 92069
866-523-7774

© Copyright 2018 JQ Green America Inc.