


LBDTubular COBLine Series



Key Features & Benefits

The new COB LED source provides unified color and light output and is ideal to replace **BA15D base** lighting fixtures. Available: 3W, 5W options. This bulb is highly versatile and offers significant energy savings and environmentally friendly. Light output is 360° which is perfect for even dispersion applications.

Technical Specifications:

Model Name	JQ-LBD-C03K30 [3000K]	JQ-LBD-C05K30 [3000K]
Photo		
Halogen Replacement	30W	50 Watt
Shape & Base	BA15D	BA15D
Operating Voltage:	120VAC	120VAC
Power consumption:	3W	5 Watt
Dimmable: *	Yes	Yes
Dimensions:	0.49"x0.34"x1.07"	0.56"(D)x1.46"
CRI:	86	86
CCT Option:	3000K	3000K
Luminous Flux:	300lm	500lm.
Operating Temperature:	-20° C- +50° C	-20° C- +50° C
Storage Temperature	-30° C- +60° C	-30° C- +60° C
IP Rating	IP67	IP67
Safety Certification:	ETL, FCC Compliance	ETL, FCC Compliance
Rated Lifespan:	>25,000hrs.	>25,000hrs.

Notes Wattage +/-10%; Lumen Values +/-5Lms. CRI +/- 5% ; Dimmable* fully tested with LUTRON© DVCLDVEL etc.