INTERBEAM ACCENT 12V

5311



LANDSCAPE LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Landscape Interbeam accent luminaire. One fixture replaces all older halogen landscape accent lights

(1)25/1

FEATURES

- Continuously Adjustable Beam Angles. Indexed at 20^o, 35°, 60°
- IP66 rated, Protected against high-pressure water jets
- Corrosion resistant aluminum
- · Factory sealed water tight fixtures
- Constant output for 9V-15V input
- Can be used as an uplight or downlight
- 2700K or 3000K color temperature
- Mounting stake, detachable shroud, 6' lead wire and direct burial gel filled wire nuts included
- MLV dimmable with remote MLV dimmers

	Color Temp		Finish	
5311 12V	27	2700K Warm White	BK	Black on Aluminum
	30	3000K Pure White	BZ	Bronze on Aluminum

5311-30____

Example: 5311-30BZ

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585

SPECIFICATIONS

Input:	9 -15VAC
Power:	6W / 7.7VA
Brightness:	475 lm
Beam Angle:	20° to 60°
CRI:	85
Rated Life:	70,000 hours

INTERBEAM ACCENT 12V 5311



LANDSCAPE LIGHTING

Accessories 5111-SNOOT-BK Black on Aluminum Accent Snoot Shields lamp and reduces glare 5111-SNOOT-BZ Bronze on Aluminum 5111-LSHR-BK Black on Aluminum Reduce glare. Ideal for downlighting application 5" Long Shroud 5111-LSHR-BZ Bronze on Aluminum 9000-ST9-BZ Additional Stake Bronze Durable PVC stake Includes three 7 inch threaded stainless steel stabilizing pins for 5000-SCP-BZ Bronze on Aluminum Surface Mount ground mounting or surface mounts with four screws or over a 5000-SCP-BK Flange/Stake Black on Aluminum iunction box Heavy duty stainless steel spike to position fixture 9000-SP9-BZ Guardian Mount Stainless Steel Formed from a single piece of metal Gutter Mount 5000-GM-BZ Stainless Steel universal mounting bracket for gutter mounting Stainless Steel 5000-GM-Bk Bracket fixture 5000-TCP-BZ Tree Mount Bronze on Aluminum Bronze on Aluminum box with Stainless steel mounting screws. 5000-TCP-BK Black on Aluminum Two 1/2" NPT threaded holes Junction Box LENS-16-AMB Amber LENS-16-FR Frosted LENS-16-GRN Green Optics LENS-16-SPR Spread Enhances saturation of florals and foliage LENS-16-RED Red LENS-16-BEL Elongating LENS-16-BLU Blue 5000-X18-BZ 18 in 5000-X04-BZ 4 in 5000-X18-BK 18 in 5000-X04-BK 4 in 5000-X24-BZ 24 in 5000-X08-BZ Extends distance between Accent light and 8in Extension Rods 5000-X24-BK 24 in 5000-X08-BK Surface Mount Canopy, Stake, or Tree Mount box 8 in 5000-X12-BZ 12 in 5000-X12-BK 12 in Rod L-Coupler 5000-LCO-BZ Bronze Magnetic Transformers Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories 0. 9075-TRN-SS 9150-TRN-SS 9300-TRN-SS 9600-TRN-SS 150W Max 300W Max 600W Max 75W Max

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. MAR 18 2021