





#### PRODUCT DETA s:

- A wiring kit and ground spike are supplied
  Suitable for use in wet (outdoor direct rain) locatior United States UL Underwriters Laboratories & CSA as defined by NEC and CEC. Meets Canadian Standards Association Product
- Safety Standards Photometrics are based off bulb photometrics. For more information on how to control your landsd pe lighting via the Hinkley Home Automation App, click here.
- Collections boast a breadth of fixtures defined by coordinating composition, Our Estate enduring architecture, and time-honored craftsmanship, designed to meet the needs of expansive properties with extended outdoor living spaces. From the entrance of your driveway to the depths of your backyard, these collections provide cohesive design for stately exteriors. 5-year finish warranty
- LED Bulbs carry a 3-year limited warranty
- · The Coastal Elements Collection offers versatile designs, constructed of composite materials and coated with anti-fading finishes, for maximum durability in harsh climates

## REPUBLIC

### 15558BK-LL

LED PATH LIGHT

Republic's striking double frame design, constructed from a composite material and treated with an antifading agent for maximum durability, is at home on the coast or a country lodge. The Oil Rubbed Bronze, Satin Nickel and Black resilience finishes feature a 5-year warranty and are resistant to rust and corrosion. Vintage filament bulbs are recommended to complete a stylish look.

DETAILS	
FINISH:	Black
MATERIAL:	Composite
GLASS:	Etched
DIMMABLE:	YES - MLV ON TRANSFORMER PRIMARY

#### DIMENSIONS

WIDTH:	6"
HEIGHT:	24"
DEPTH:	5.8
WEIGHT:	2lb

#### LICHT SOURCE

LIGHT SOURCE	
LIGHT SOURCE:	Socketed
LED NAME:	00T5-27LED-1.5
VOLTAGE:	12v
COLOR TEMP:	2700
LUMENS:	150
CRI:	90
INCANDESCENT EQUIVALENCY:	1 x 25w
DIMMABLE:	YES - MLV ON TRANSFORMER PRIMARY
TRANSFORMER REQUIRED:	Yes

MOUNTING	
LEAD WIRE:	1 X 36"

SHIPPING	
CARTON LENGTH:	26
CARTON WIDTH:	7.5
CARTON HEIGHT:	7.5
CARTON WEIGHT:	4.5

# HINKLEY

HINKLEY 33000 Pin Oak Parkway Avon Lake, OH 44012