


SINGLE ADJUSTABLE FLOOD LIGHT

Endurance™ - WP-LED514

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Die cast aluminum factory sealed luminaire with patent pending design for a water and dust proof IP66 rated outdoor.

FEATURES

- Rotate to continuously adjust beam angles indexed at 15°, 25°, 40°, 60°
- IP66 and ETL & cETL Wet Location Listed
- Factory-Sealed LED Light Engine
- Die-Cast Aluminum Construction
- 120V Direct Wire - No Driver Needed
- Safety cable and canopy included
- Comes with extension rod kit to extend up to 44" total
- Detachable Shroud
- Safety cable recommended for extensions over 36"
- One 6", one 12", one 24" field interchangeable rods included

SPECIFICATIONS

Construction: Die-cast aluminum

Power: Line Voltage input (120V)

CRI: 85

Dimming: 100% - 10% with Electronic Low Voltage (ELV) dimmer

Finish: Architectural Bronze, Black, Graphite and White

Operating Temp: -40°F to 122°F (-40°C to 50°C)

Standards: IP66, Wet Location, ETL & cETL Listed

Rated Life: 50,000 hours

ORDER NUMBER

	Power	Comparable	Beam	Delivered Lumens	CBCP	Color Temp	Finish
WP-LED514 Single	15W	150W PAR38	15°	600	4145	30 3000K	ABZ Architectural Bronze ABK Architectural Black AGH Architectural Graphite AWT Architectural White
			60°	985	875		
			15°	695	4800	40 4000K	
			60°	1140	1015		

Example: **WP-LED514-40-AGH**

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585